

**PRODUCT SELECTION MATRIX**

# MARK-3<sup>®</sup>

## SERIES



			MK-3	MK-3D	MK-3U	
SPECIFICATIONS	Performance (standard NFPA Conditions)	Flow @ 100 PSI (6.9 BAR)		78 GPM (295 lpm)		
		Flow @ 150 PSI (10.3 BAR)		65 GPM (246 lpm)		
		Flow @ 200 PSI (13.8 BAR)		38 GPM (144 lpm)		
		Maximum Pressure		380 PSI (26.2 BAR)		
		Maximum Flow		98 GPM (371 lpm)		
	Engine Type	Air Cooled Gasoline		WATERAX 185cc		
	Engine Max Power	[Torque]		"10 hp (7.5 kW) @ 5,500 rpm [8.9 lb-ft (12 Nm) @ 5000 RPM]"		
	Pump Type	High Pressure		4-Stage Centrifugal Pump		
	Pump Standard Connections	Intake		2" Male NPSH	2" Male NPSH	1-1/2" Male NH
		Discharge		1-1/2" Male NPSH	1-1/2" Male NPSH	1-1/2" Male NH
Fuel Connector			Mercury	Mercury	SAE 45	
Frame			Backpackable Frame			
Dry Weight*			58.3 lbs (26.4 kg)			

\* Approximated and varies based off option selections

OPTIONS	Decompression Switch		-	S	-	
	Fuel Tank	Air Transport		0	0	-
		Metal Jerry Can		-	-	0
	Suction Thread Protector		0	0	-	
	Discharge Thread Protector		0	0	-	
	Discharge Gauge		0	0	0	
	Check Valve Monitor		0	0	0	
	Primer	Hand Primer		0	0	0

Standard      s  
Option        o  
Not Applicable —